



アイボルト JIS B 1168-1994(M 矽)

| 呼び (ネジ径) d | 寸法(mm) | | | | | | | | 使用荷重kN (kgf) | 重量 (kg) |
|------------------|--------|-----|------|-----|-----|-----------|-----|------|----------------------|------------|
| | d2 | d4 | k | d3 | h | H (参考) | b | d2 | 垂直吊り45度吊り (2個につき) | |
| 8 | 32.6 | 20 | 6.3 | 16 | 17 | 33.3 | 15 | 6 | 0.785(80) | 0.03 |
| 10 | 41 | 25 | 8 | 20 | 21 | 41.5 | 18 | 7.7 | 1.47(150) | 0.06 |
| 12 | 50 | 30 | 10 | 25 | 26 | 51 | 22 | 9.4 | 2.16(220) | 0.12 |
| 16 | 60 | 35 | 12.5 | 30 | 30 | 60 | 27 | 13 | 4.41(450) | 0.22 |
| 20 | 72 | 40 | 16 | 35 | 35 | 71 | 30 | 16.4 | 6.18(630) | 0.4 |
| 24 | 90 | 50 | 20 | 45 | 45 | 90 | 38 | 19.6 | 9.32(950) | 0.8 |
| 30 | 110 | 60 | 25 | 60 | 55 | 110 | 45 | 25 | 14.7(1,500) | 1.54 |
| 36 | 133 | 70 | 31.5 | 70 | 65 | 131.5 | 55 | 30.3 | 22.6(2,300) | 2.83 |
| 42 | 151 | 80 | 35.5 | 80 | 75 | 150.5 | 65 | 35.6 | 33.3(3,400) | 4.1 |
| 48 | 170 | 90 | 40 | 90 | 85 | 170 | 70 | 41 | 44.1(4,500) | 5.88 |
| 64 | 210 | 110 | 50 | 110 | 105 | 210 | 90 | 55.7 | 88.3(9,000) | 11.6 |
| 80×6 | 266 | 140 | 63 | 130 | 130 | 263 | 105 | 71 | 147(15,000) | 21.5 |
| 100×6 | 340 | 180 | 80 | 170 | 165 | 335 | 130 | 91 | 196(20,000) | 46.5 |